



SCRUBBER DRIERS - WALK BEHIND

CT45

MAX PRODUCTIVITY

1750 m²/h

BATTERIES
RUNNING TIME

2,5 h

WATER TANK
RUNNING TIME

50'
working session



BATTERIES AND BATTERY CHARGER INCLUDED

MOST FREQUENTLY USE



INNOVATIONS



ECO
SELECT



DBL™
DOUBLE
BATTERY
LIFE



SLSTM™
SELF
LEVELING
SYSTEM



BACTERIA
CONTROL

SPECS



FOLDABLE HANDLE



PRESET WORKING
PROGRAMS



THREE-PHASE VACUUM MOTOR

TECHNICAL DATA

		CT45 B50	CT45 BT50	CT45 C50
Code		LPTB01520	LPTB02695	LPTB01103
PERFORMANCE				
Max theoretical productivity	m2/h	1750	1750	1750
Cleaning path	mm	500	500	500
Water tank capacity (solution recovery)	l	40/45	40/45	40/45
Max running time	min	140	140	Unlimited
Voltage	V-Ah	24(2x12)-74 GEL	24(2x12)-74 GEL	230-50/60
Installed power	W	550	550	400
Brush pressure	kg	16/25	16/25	16/25
Squeegee width	mm	730	730	730
Max speed	km/h	3,5	3,5	3,5
Weight	kg	110	110	65
Dimension (LxWxH)	mm	821x576x1220	821x576x1220	821x576x1220

STANDARD ACCESSORIES

	CT45 B50	CT45 BT50	CT45 C50
BRUSHES			
BRUSH	SPPV01332	SPPV01332	SPPV01332
SQUEEGEE BLADES			
LATEX FRONT BLADE	MPVR06287 - 815mm	MPVR06287 - 815mm	MPVR06287 - 815mm
LATEX REAR BLADE	MPVR06288 - 715mm	MPVR06288 - 715mm	MPVR06288 - 715mm

CONSUMABLES (Codes available on price list)

BRUSHES



PADS/SUPER PADS



SQUEEGEE BLADES



OPTIONAL ACCESSORIES

CODE: MPVR05966
SPLASH GUARD



CODE: KTRI02140
CHEM DOSE



CODE: KTRI02257
EXTERNAL SUCTION KIT



CODE: PRCH00578
BIOSAN RAPIDE WT
(30PCS/30DAYS)



BATTERIES AND BATTERY CHARGERS

BATTERIES	N°	CHARACTERISTICS	DIMENSION	RUNNING TIME	BATTERY CHARGERS
IPC AGM battery BAAC00117	2	12V 74 Ah (C5)	257x172x212	150 min	On board battery charger 24V 10Ah KTRI02245
EXIDE gel battery BAAC00124	2	12V 63 Ah (C5)	261x171x210	130 min	On board battery charger 24V 10Ah KTRI02245

RECOMMENDED BATTERIES AND BATTERY CHARGERS