

## Comfort S-R 90

### LEVEL



STOP



### Equipped with:

- Suitable for maintenance and deep cleaning of medium and large areas (up to 4.500 m<sup>2</sup>) with a considerable reduction of cleaning costs
- More than 50 kg of constant pressure on the brushes
- Large load tank capacity, resulting in reduced number of stops and maximum use of battery charge for effective operation of the machine
- Stability even when fully loaded
- Front independent wheel-drive with tight steering radius
- Easy access to electrical components
- Automatic brush plate lifting system
- Automatic squeegee lifting system
- Automatic squeegee lifting while reverse going
- Automatic device that stops brushes and detergent water outflow when the machine is stationary
- Antifoam device
- Self-levelling brushes
- High-performance batteries resulting in high-working efficiency.

**\* New, standard on machines starting from 2022, compatible with all previous machine models**

### STANDARD EQUIPMENT

\*



- 2 x 5.511.2233  
PP brush Ø 457 mm - 18"



- 4.508.1196  
Front squeegee blade L.1027 mm  
Shore 40 Th. 3 mm
- 4.508.1195  
Rear squeegee blade L.1150 mm  
Shore 33 Th. 4 mm

	Comfort S-R 90
code	8.575.0010
power supply	24V
scrubbing/squeegee width	900/1000 mm
max working capacity	6200 m <sup>2</sup> /h
solution tank capacity	140 l/36.99 gal
recovery tank capacity	150-180 l/39.6-47 gal
traction type/power	front motorwheel/1000 W
RPM/pressure on the brushes	150/50 kg/176 lbs
brush motor power	1250 W
max gradient empty/full tank	10%/7%
depression/vacuum motor	1734 mmH <sub>2</sub> O/550W
dimensions/weight	180x103x150 cm/264 kg

**OPTIONAL**



Quick lock recovery tank cap allows for fast and easy cleaning and sanitization of the tank; the tilting tank together with a large size drain hose allow the complete emptying of the tank and the removal of any type of solid dirt. The antifoam device protects suction motor, as well as the electronic floating switch that stops suction when the tank is full.



- 0.107.0008 Battery box Pb-acid 24V 500Ah C5
- 0.107.0011 Gel battery box 24V 400Ah C5



- 0.108.0003 Battery Charger 24V/36V 50/60A - 220-240/50-60



- 4.508.1251 Polyurethane front blade L.1027 TH. 3
- 4.508.1252 Polyurethane rear blade L.1150 TH. 4

Comfortable steering wheel. User friendly control panel, provided with hour meter, speed adjustment knob and detergent solution low level warning light. All motors are protected by thermal breakers.



\*



- 2x 5.511.2234 Tynex brush Ø 457 mm-18"
- 2x 5.511.2235 PP 0,3 brush Ø 457 mm-18"
- 2x 5.511.2236 PES brush Ø 457 mm-18"

\*



- 2x 5.511.2237 EWU pad driver Ø 457 mm-18"



50 kg of continuous brush plate pressure with Self Leveling System to strongly and deeply removing any kind of dirt on any kind of floor. Strong oil-proof polyurethane wheels. 500 Ah C5 battery box allowing continuous working time up to 5 hours.



- 6.508.0150 - Ø 457 mm-18"- beige (5 pcs.)
- 6.508.0151 - Ø 457 mm-18"- green (5 pcs.)
- 6.508.0142 - Ø 457 mm-18"- black (5 pcs.)

Built with strong components, Comfort S-R have been designed to resist even to extreme stresses; the frame is made of steel profiles with a thickness varying from 5 to 12 mm, protected with a high resistance corrosion-proof paint.

