

202 DS - INDUSTRIAL SINGLE PHASE



R

CERAMICS AND POTTERY INDUSTRIES









CLEANING CONTRACTORS

- ✓ Largest surface filter in its category
- ✓ Integrated filter cleaning system
- ✓ Complete steel construction
- ✓ Extractable collection container with optional use of disposable bags
- ✓ Two powerful by pass motors with independent cooling



1

- ✓ Low noise level
- ✓ Compact and mobile
- ✓ Easy filter replacement
- \checkmark Accessory kit as standard

SUCTION UNIT		
Voltage	V - Hz	230 - 50
Power	kW	2,3
Max waterlift	mmH2O	2.500
Max air flow	m³/h	360
Suction inlet	mm	50
Noise level (EN ISO 3744)	dB(A)	76
FILTER UNIT		
Filter Type		Cartridge
Surface - Diameter	cm²-mm	30.000 - 360
Material - Efficiency	IEC 60335-2-69	Polyester - M
Air load on filter	m³/m²/h	120
Cleaning system		Dustop
Discharge system		Roll-out container
Transport capacity	kg/h	20
VOLUME		
Dimensions	cm	59x48x110h

kg

All data mentioned in this document may change without notice. Tutti i dati riportati in questo documento potrebbero variare senza preavviso

Weight

www.delfinvacuums.it delfin@delfinvacuums.it

35

delfin

SUCTION UNIT

The suction is provided by two by-pass motors, using carbon brushes, operated by independent switches and placed inside a sturdy steel casing, filled with soundproofing material.

FILTER UNIT

It is possible to clean the filter using the Dustop, an integrated reverse pulse system: by closing the suction inlet and opening a flap in the filter chamber, the airflow generated by the motor cleans the filter thoroughly and safely, maintaining constant suction performance and preventing any dispersion of dust in the environment. The polyester cartridge filter placed inside the filter chamber guarantees a large filter surface and prevents the clogging of the filter.

COLLECTION UNIT

The vacuumed material is collected into a wheeled steel container, which can be extracted for easy disposal and can be used with optional disposable bags, for safer and handier disposal.

- ✓ ABSOLUTE HEPA FILTER
- ✓ ANTISTATIC FILTER CLASS M
- ✓ HEAT RESISTANT FILTER (UP TO 250° CELSIUS)
- ✓ STAINLESS STEEL COLLECTION TANK
- ✓ STAINLESS STEEL TANK AND FILTER CHAMBER
- ✓ TOTAL STAINLESS STEEL CONSTRUCTION
- ✓ LONGOPAC BAGGING SYSTEM
- ✓ REMOTE CONTROL
- ✓ OTHER VOLTAGES AND FREQUENCIES AVAILABLE UPON REQUEST
- ✓ ATEX CERTIFICATION

All data mentioned in this document may change without notice. Tutti i dati riportati in questo documento potrebbero variare senza preavviso www.delfinvacuums.it delfin@delfinvacuums.it