

## Comfort XXS



Only code  
8.579.0002

**LEVEL**



**CHARGER**  
Only code  
8.579.0002  
8.579.0011



### STANDARD EQUIPMENT



\*  
• 2 x 5.511.2212  
PP Brush Ø 330 mm - 13"



• 4.508.1619  
Front squeegee blade  
L.960 mm Th. 2,5 mm

• 4.508.1618  
Rear squeegee blade  
L.1000 mm Th. 3 mm



• 0.108.0054  
On-board Battery charger  
24V 20A  
(only for models code:  
8.579.0002 - 8.579.0011)



• 2 x 0.107.0063  
Gel battery 12V 105 A/C  
5/120A C20  
(only for model code:  
8.579.0002)

### Equipped with:

Designed for the maintenance and deep cleaning of large areas (up to 3200 m<sup>2</sup>.) with a very important reduction of cleaning cost. Very compact size and great maneuverability like walk behind models: suited for maintenance cleaning.

- 32 kg. of constant pressure on the brushes.
- Double counter rotating brush (66 cm of scrubbing width) obtaining better stability and constant pressure.
- Great working autonomy thanks to the possibility to use 4 batteries 6 V 240 Ah and to rear wheel-drive.
- Large load tank capacity (real load of 85 l. ), resulting in reduced numbers of stops and maximum use of battery for effective operation of the machine.
- Ergonomic steering wheel of new design with user friendly controls and digital display.
- Easy access to electrical components.
- Inspection cover for fast and easy cleaning and sanification of dirt water tank.
- Automatic device that stops brushes and detergent water outflow when the machine is stationary.
- Self-levelling brush plate.
- **Automatic detergent dosing system.**

\* **New, standard on machines starting from 2022, compatible with all previous machine models**

	Comfort XXS 66 BT	Comfort XXS 66 BT	Comfort XXS 66 BT
code	8.579.0001	8.579.0011	8.579.0002
power supply	24V	24V (battery charger included)	24V (batteries and battery charger included)
scrubbing/squeegee width	660/855 mm	660/855 mm	660/855 mm
max working capacity	3250 m <sup>2</sup> /h	3250 m <sup>2</sup> /h	3250 m <sup>2</sup> /h
solution tank capacity	80 l/19.81 gal	80 l/19.81 gal	80 l/19.81 gal
recovery tank capacity	80-85 l/19.81-21.13 gal	80-85 l/19.81-21.13 gal	80-85 l/19.81-21.13 gal
traction	rear wheel-drive/400 W	rear wheel-drive/400 W	rear wheel-drive/400 W
RPM/pressure on the brushes	170/32 kg/70.54 lbs	170/32 kg/70.54 lbs	170/32 kg/70.54 lbs
brush motor power	2 X 400 W	2 X 400 W	2 X 400 W
max gradient empty/full tank	13%/10%	13%/10%	13%/10%
depression/vacuum motor	1300 mmH <sub>2</sub> O/400 W	1300 mmH <sub>2</sub> O/400 W	1300 mmH <sub>2</sub> O/400 W
dimensions/weight	123x63x121 cm/139 kg	123x63x121 cm/142 kg	123x63x121 cm/217 kg



Great working autonomy thanks to the possibility to use 4 batteries 6 V 180 Ah granting continuous working up. Possibility to use also 2 batteries 12V. Less battery consumption thanks to rear wheel-drive. Large load tanks made of shock and acid proof polyethylene (real load of 85 l.), avoiding frequent stop for refilling.

User friendly control panel. Steering wheel with digital controls and display. Squeegee and brush plate mechanical and user friendly lifting lever: min. maintenance cost training time for the users. Scrubbing unit with double brush with brush plate made of steel for a great pressure (32 Kg.) on the floor resulting in an easy and deep cleaning of any kind of dirt.



Rear wheel-drive on 2 wheels allows the machine to get over remarkable slopes. Detergent solution is cleansed by an external completely accessible filter, that holds any impurities, thus protecting the solenoid valve. The easy access to all internal components of XXS make it possible to reduce maintenance cost. Detergent tank 2lt.

The comfortable and ergonomic seat allows the operator to work effortless for a long time, improving productivity. Its very compact size make it perfect to work in small areas where walk behind models are usually used. The use of XXS makes working easier and quicker with a huge saving of time.



**OPTIONAL**



- 4 x 0.107.0004 Tubular battery Pb-acid 6V 180Ah C20 + 2 x 5.511.0561 connection cable batteries



- 4 x 0.107.0072 Gel battery 6 MFP 180 6V 180Ah C5 + 2 x 5.511.0561 connection cable batteries



- 2 x 0.107.0002 Tubular battery Pb-acid 12V 118 Ah C5



- 0.108.0080 Battery Charger 24V 30A 220-240/50-6



- 4.508.1594 Polyurethane front blade L.960 TH.3 Sh.40
- 4.508.1596 Polyurethane rear blade L.1000 TH.4 Sh.40




- \* • 2 x 5.511.2208 Tynex brush Ø 330 mm-13"
- 2 x 5.511.2209 PP 0,3 brush Ø 330 mm-13"
- 2 x 5.511.2210 PES brush Ø 330 mm - 13"



- \* • 2 x 5.511.2211 EWU pad driver Ø 330 mm-13"



- 6.508.0030 - Ø 340 mm - 13"- beige (5 pcs.)
- 6.508.0037 - Ø 340 mm - 13"- green (5 pcs.)
- 6.508.0044 - Ø 340 mm - 13"- black (5 pcs.)



- 6.505.0062 Flashing light